

Fiber Distribution Box (FDB) 8 Ports



FEATURES

- IP 68 Rating for external use
- Lockable door for added security
- Integrated cable tie points for securing incoming cable
- Up to 8 splice & SC connection points
- Accepts loose tube, distribution and pre-terminated cables
- Integrated bend radius protection
- Sealing glands for 3 incoming cables
- Waterproof sealing for 8 exiting cables
- Supplied with 8 heat shrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixings and tie wraps
- RoHS, REACH & SvHC compliant

APPLICATIONS

- Premise installations, telecommunication networks
- Ethernet, Fiber Channel, ATM, LAN, MAN and WAN
- Indoor/outdoor applications
- FTTA application

TECHNICAL CHARACTERISTIC

Parameters	Value
Height	230mm
Width	207mm
Depth	53mm
IP Rating	IP68
Suitable Adapter Type	SC Simplex
Number of Exit Ports	8
Number of Cable Entry	3
Material	+ABS
Operating temperature	-40°C to +50°C
Color	White
Net Weight	1.18Kg
Compliant to	RoHS, REACH, SvHC

ORDERING INFORMATION

Part No.	Description
ANX-FDB24	IP65 Indoor & Outdoor Fiber Distribution Box (FDB) 8 Ports