



Fiber Optic DP Pedestal



FEATURES

- Made of electro-galvanized steel sheet with polyester epoxy powder coating finishing
- Protection Insulation IP65
- Multiple installation options: floor mounted or on top of plinth
- Adapter type: FC, SC, ST, LC
- Capacity up to 24 port. However, others capacity can be customized as required
- Quick field installation
- It's designed especially for outdoor optical nodes in access network
- Perfect design for easy fiber cable routing & friendly maintenance of fiber cable
- Built-in compartment for installation of fiber optic splitter. Such as 1 x 8, 1 x 16 and so on.
- Suitable for housing, commercial & factory industrial area

APPLICATIONS

- FTTH, FTTO, FTTX
- Fiber Optic Telecommunication
- CATV System
- LAN (Local Area Network)

TECHNICAL CHARACTERISTIC

Parameters	Value
Operating Temperature	-45°C to +85
Injected Air Pressure	≤ 85% (+30°C)
Colour	Black
Dimension	562mm x 390mm x 230mm (6, 8, 12, 16, 24 port)

ORDERING INFORMATION

Part No.	Connector	Fiber Port	Cable Type
ANX-DPP = Annexecom DP Pedestal	FC = FC FCA = FC/APC LC = LC LCA = LC/APC SC = SC SCA = SC/APC ST = ST/UPC	06 = 6 ports 08 = 8 ports 12 = 12 ports 16 = 16 ports 24 = 24 ports	SM = Single Mode OS1 / OS2 MM = Multi Mode OM1 / OM2 / OM3 OM4 / OM5
ANX-DPP	aa	bb	zz