




Rack Mount Fiber Patch Panel



Blank Patch Panel



8 Port SC Simplex / LC Duplex Plate



8 Port ST Simplex / FC Simplex Plate



6 Port SC Duplex / LC Quad Plate



Blanking Plate



Adapters

FEATURES

- Made of cold-roll steel sheet with electro galvanized finishing
- Removable panel design can meet different requirements
- Suitable for 19" and 23" rack mounted
- Adapter type: FC, SC, ST, LC
- Capacity up to 48 ports
- Quick field installation
- Retractable splicing tray
- Special design ensures the excess fiber cords and pigtails in good order

APPLICATIONS

- Fiber Optic Telecommunication
- Optical network equipment
- CATV
- LAN (Local Area Network)
- CWDM (Coarse Wavelength Division Multiplex)

TECHNICAL CHARACTERISTIC

Parameters	Value
Operating Temperature	-25°C to +40°C
Storage Temperature	-25°C to +55°C
Relative Humidity	≤ 85% (+30°C)
Colour	Black or Beige
Dimension	1U x 485mm x 220mm (4, 6, 12, 24, 36, 48 ports)

ORDERING INFORMATION

Part No.	Connector	Fiber Port Qty	Adapter Count	Connector Type
ANX-ERMFDP = Annexcom Rack Mount Fiber Patch Panel	FC = FC FCA = FC/APC SC = SC SCA = SC/APC LC = LC LCA = LC/APC	04 = 4 ports 06 = 6 ports 12 = 12 ports 24 = 24 ports 36 = 36 ports 48 = 48 ports	SX = Simplex DX = Duplex QX = Quadplex	SM = Single Mode OS1 / OS2 MM = Multi Mode OM1 / OM2 / OM3 OM4 / OM5
ANX-ERMFDP	aa	bb	xx	yy